

Termostroj Termo Blok		6	9	12	14	16	18	20	22	24	28	32	36	40
Snaga	(kW)	6	9	12	14	16	18	20	22	24	28	32	36	40
Zapremina kotla	(l)	6	6	6	6	6	10	10	10	10	22	22	22	22
Ekspanziona posuda	(l/bar)	8/0,8	8/0,8	8/0,8	8/0,8	8/0,8	10/0,8	10/0,8	10/0,8	10/0,8	12/0,8	12/0,8	12/0,8	12/0,8
Odlazni/povratni priključak sistema grejanja	(R)	3/4"	3/4"	3/4"	3/4"	3/4"	1"	1"	1"	1"	1"	1"	1"	1"
Temperaturni opseg vode u sistemu grejanja	(°C)	20-90	20-90	20-90	20-90	20-90	20-90	20-90	20-90	20-90	20-90	20-90	20-90	20-90
Temperaturni opseg vode u PTV rezervoaru	(°C)	10-65	10-65	10-65	10-65	10-65	10-65	10-65	10-65	10-65	10-65	10-65	10-65	10-65
Maksimalni radni pritisak (sistem grejanja)	(bar)	3	3	3	3	3	3	3	3	3	3	3	3	3
Struja (230V - 50/60Hz)	(Amper)	26,1	39,2	-	-	-	-	-	-	-	-	-	-	-
Preporučeni osigurači (230V - 50/60Hz)	(Amper)	32	50	-	-	-	-	-	-	-	-	-	-	-
Struja (400V - 50/60Hz)	(Amper)	3x8,7	3x13,04	3x17,39	3x20,29	3x23,19	3x26,09	3x28,99	3x31,88	3x34,78	3x40,58	3x46,38	3x52,17	3x57,97
Preporučeni osigurači (400V - 50/60Hz)	(Amper)	10	16	25	25	32	32	40	40	40	50	63	63	63
Grejači	(kW)	3x1+3x1	3x2+3x1	3x2+3x2	3x2,66+3x2	3x2,66+3x2,66	3x2+3x2+3x2	3x2,66+3x2+3x2	3x2,66+3x2,66+3x2	3x2,66+3x2,66	(3x2,66+3x2)+3x2,66+3x2	(3x2,66+3x2,66)+3x2,66+3x2,66	(3x2,66+3x2,66)+3x2,66+3x2,66	(3x2,66+3x2,66)+3x2,66+3x2,66
Presek priključka	(mm ²)	3x6 v. 5x2,5	3x10 v. 5x2,5	5x4	5x4	5x4	5x6	5x6	5x6	5x10	5x10	5x10	5x16	5x16
Tip FI releja	(Amper)	40/0,03 v. 25/0,03	60/0,03 v. 25/0,03	25/0,03	25/0,03	25/0,03	40/0,03	40/0,03	40/0,03	40/0,03	63/0,03	63/0,03	63/0,03	63/0,03
Visina kotla	(mm)	930	930	930	930	930	930	930	930	930	930	930	930	930
Dubina kotla	(mm)	290	290	290	290	290	290	290	290	290	290	290	290	290
Širina kotla	(mm)	330	330	330	330	330	400	400	400	400	474	474	474	474
Težina kotla	(kg)	40	40	40	40	40	46	46	46	46	53	53	53	53