

Termostroj Termo Extra		52	56	60	64	72	80	88	96
Snaga	(kW)	52	56	60	64	72	80	88	96
Zapremina kotla	(l)	19	19	19	32	32	32	32	32
Odlazni/povratni priključak sistema grejanja	(R)	6/4"	6/4"	6/4"	2"	2"	2"	2"	2"
Temperaturni opseg vode u sistemu grejanja	(°C)	20-90	20-90	20-90	20-90	20-90	20-90	20-90	20-90
Maksimalni radni pritisak (sistem grejanja)	(bar)	2,5	2,5	2,5	2,5	2,5	2,5	2,5	2,5
Struja (400V - 50/60Hz)	(Amper)	3 x 75,36	3 x 81,16	3 x 86,96	3 x 92,75	3 x 104,35	3 x 115,94	3 x 127,54	3 x 139,13
Preporučeni osigurači (400V - 50/60Hz)	(Amper)	100	100	100	125	125	160	160	160
Grejači	(kW)	(8)+(8+8)+(8+8+6+6)/6=3x2 i 8=3x2,66/	(8)+(8+8)+(8+8+8+8)/8=3x2,66/	(8)+(8+8)+(8+8+8+6+6)/6=3x2 i 8=3x2,66/	(8)+(8+8)+(8+8+8+8)/8=3x2,66/	(8)+(8+8+8)+(8+8+8+8)/8=3x2,66/ +8+8)/8=3x2,66/ +8+8)/8=3x2,66/	(8)+(8+8+8)+(8+8+8+8)/8=3x2,66/ +8+8+8)/8=3x2,66/ +8+8+8)/8=3x2,66/	(8)+(8+8+8)+(8+8+8+8)/8=3x2,66/ +8+8+8)/8=3x2,66/ +8+8+8)/8=3x2,66/	(8)+(8+8+8)+(8+8+8+8)/8=3x2,66/ +8+8+8)/8=3x2,66/ +8+8+8)/8=3x2,66/
Presek priključka	(mm ²)	5x25	5x35	5x35	5x35	5x50	5x50	5x70	5x70
Tip FI releja	(Amper)	0,3	0,3	0,3	0,3	0,3	0,3	0,3	0,3
Visina kotla	(mm)	930	930	930	930	930	930	930	930
Dubina kotla	(mm)	310	310	310	310	310	310	310	310
Širina kotla	(mm)	400	400	400	400	400	400	400	400
Težina kotla	(kg)	52	52	52	81	81	81	81	81